

SORTING GRAPPLE

MG
150

PRODUCT DATASHEET




FIG. 01 · MG-150 · EXTERIOR VIEW · RAL 7026

Compact · 1.2–3 t carriers: a protected, efficient and versatile layout with a fixed cylinder and internally routed hoses.

01

Lightweight body

Optimized structure controls weight while retaining rigidity.

02

Protected hose routing

The fixed-cylinder layout protects hoses from snagging and impact.

03

Low oil-flow demand

Recommended oil flow: 25 L/min, reducing hydraulic matching requirements.

Technical specifications

PRODUCT DATA

Carrier weight	1.2–3 t	Closing force	15 kN
Weight	155 kg	Open/close pressure	220 bar
W Shell width	450 mm	Open/close oil flow	25 L/min
A Maximum opening	800 mm	Cylinders	1
Shell volume	70 L	Rotation motors	1
D Closed height	700 mm		

CONNECTION OPTIONS

- DIRECT PIN-ON
- CW
- MS
- SQ / OPEN-S

SHELL OPTIONS

Alternative shell configurations available on request.



OPTION 1 · Grid



OPTION 2 · Closed



OPTION 3 · Toothed




Fig. 02 · Dimension reference (not to scale): D · A · W

D 700 mm · A 800 mm · W 450 mm

MHA CONSTRUCTION EQUIPMENT

info@mhaconstructionequipment.com · www.mhaconstructionequipment.com

Data based on MHA Sorting Grapple EN, ED. 2026 V1.0. Specifications are subject to change without notice.

OPEN-S MEMBER

